

## Enclosure air conditioner, 5100 BTU



### Description

<b>Order Number:</b>	871525201USL
<b>Brand Name:</b>	SOLITHERM PROGRESSIVE
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection:</b>	IP 56 / Type 12, 3, 3R, 4, 4X
<b>Included:</b>	With metal mesh filter
<b>Approvals:</b>	CE, UL(ACVS), cULus
<b>UL File Number:</b>	SA32278

## Technical data

<b>Cooling capacity 95F/95F:</b>	5120 BTU @ 60 Hz
<b>Cooling capacity 95F/122F:</b>	3650 BTU @ 50 Hz 3820 BTU @ 60 Hz
<b>EER 95F95F:</b>	6.7 / 6.1
<b>Enclosure heater:</b>	1,000 W
<b>Compressor type:</b>	Reciprocating compressor
<b>Refrigerant / GWP:</b>	R 134a / 1430
<b>Refrigerant charge:</b>	275 g / 9.7 oz
<b>High / low pressure:</b>	435 / 87 psig
<b>Operating temperature range:</b>	-40°F - 140°F
<b>UL temperature range:</b>	-40°F - 140°F
<b>Air volume flow (system / unimpeded):</b>	Ambient: 330 / 520 cfm Enclosure: 360 / 520 cfm
<b>Mounting:</b>	Wall mounted
<b>Dimension H x W x D:</b>	35 x 15.6 x 12 inch
<b>Weight:</b>	89 lbs.
<b>Voltage / Frequency:</b>	400/460 V - 50/60 Hz 2~
<b>UL Voltage / Frequency:</b>	460 V / 60Hz 2~
<b>Current 95F95F:</b>	1.7 A @ 50 Hz 1.85 A @ 60 Hz
<b>Starting current:</b>	12 A
<b>Max. current:</b>	2.4 A
<b>Nominal power 95F95F:</b>	740 W @ 50 Hz 855 W @ 60 Hz
<b>Max. power:</b>	1.08 kW
<b>Fuse:</b>	15 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	1.4 A


**Full load current fans:** 0.4 A

---

**Connection:** 5 pole terminal block for signals  
4 pole terminal block for power  
3 pole terminal block for RS 485 MODBUS

---

**Performance graph:**



**Cut out dimensions:**

