

## Enclosure air conditioner




### Description

<b>Order Number:</b>	43050081
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection:</b>	TYPE 12
<b>Sk Hinweis:</b>	Customer: Spinner
<b>Approvals:</b>	CE, cURus, cULus


## Technical data

<b>Cooling capacity 95F/95F:</b>	2120 BTU
<b>Cooling capacity 95F/122F:</b>	1500 BTU
<b>Compressor type:</b>	Reciprocating compressor
<b>Refrigerant / GWP:</b>	R134a / 1430
<b>Refrigerant charge:</b>	127 g / 4.5 oz
<b>High / low pressure:</b>	23.3 / 5.3 bar 338 / 77 psig
<b>Operating temperature range:</b>	68°F - 131°F
<b>Air volume flow (system / unimpeded):</b>	Ambient air circuit: 256 / 324 cfm Cabinet air circuit: 118 / 147 cfm
<b>Mounting:</b>	Recessed
<b>Dimension H x W x D:</b>	28 x 14.6 x 10.2 inch
<b>Weight:</b>	61 lbs.
<b>Cut out dimensions:</b>	12.4 x 25.7 inch
<b>Voltage / Frequency:</b>	230 V ~ 50/60 Hz
<b>UL Voltage / Frequency:</b>	230 V ~ 60 Hz
<b>Current 95F95F:</b>	2.1 A
<b>Starting current:</b>	9.8 A
<b>Max. current:</b>	2.5 A
<b>Nominal power 95F95F:</b>	370 W @ 50 Hz 400 W @ 60 Hz
<b>Max. power:</b>	510 W
<b>Fuse:</b>	6 A (T)
<b>Short-circuit current rating:</b>	5 kA
<b>Connection:</b>	Connection terminal block


**Performance graph:**



**Air flow:**



**Cut out dimensions:**



## Bestellinformationen

<b>Stainless steel housing part no.</b>	43050026
<b>Taric code</b>	84158200
<b>GTIN (EAN)</b>	5350604360150