

Enclosure air conditioner




Description

Order Number:	43052081
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	TYPE 12
Approvals:	CE, cURus, cULus


Technical data

Cooling capacity 95F/95F:	2120 BTU
Cooling capacity 95F/122F:	1500 BTU
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	127 g / 4.5 oz
High / low pressure:	23.3 / 5.7 bar 338 / 77 psig
Operating temperature range:	50°F - 131°F
Air volume flow (system / unimpeded):	Ambient air circuit: 256 / 324 cfm Cabinet air circuit: 118 / 147 cfm
Mounting:	Recessed
Dimension H x W x D:	28 x 14.6 x 10.2 inch
Weight:	74 lbs.
Cut out dimensions:	12.4 x 25.7 inch
Voltage / Frequency:	400/460 V ~ 50/60 Hz 2~
UL Voltage / Frequency:	400/460 V ~ 60 Hz 2~
Current 95F95F:	1.4 A @ 50 Hz 1.2 A @ 60 Hz
Starting current:	4.3 A
Max. current:	1.6 A
Nominal power 95F95F:	440 W
Max. power:	560 W
Fuse:	2 x 3.6 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block


Performance graph:



Air flow:



Cut out dimensions:



Bestellinformationen

Stainless steel housing part no.	4305202
Taric code	84158200
GTIN (EAN)	5350604360174