

Enclosure air conditioner




Description

Order Number:	43152001
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	TYPE 12
Approvals:	CE, cURus, cULus


Technical data

Cooling capacity 95F/95F:	5560 BTU
Cooling capacity 95F/122F:	4500 BTU
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	420 g / 14.8 oz
High / low pressure:	25.5 / 6 bar 370 / 88 psig
Operating temperature range:	50°F - 131°F
Air volume flow (system / unimpeded):	Ambient air circuit: 280 / 500 cfm Cabinet air circuit: 225 / 324 cfm
Mounting:	External
Dimension H x W x D:	38.6 x 15.5 x 10.2 inch
Weight:	105 lbs.
Cut out dimensions:	36.22 x 13.19 in.
Voltage / Frequency:	400/460 V - 50/60 Hz 2~
UL Voltage / Frequency:	400/460 V ~ 60 Hz 2~
Current 95F95F:	2.9 A @ 50 Hz 2.5 A @ 60 Hz
Starting current:	5.3 A
Max. current:	3.5 A
Nominal power 95F95F:	880 W
Max. power:	1.29 kW
Fuse:	2 x 6 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block


Performance graph:



Air flow:



Cut out dimensions:



Bestellinformationen

Stainless steel housing part no.	4315202
Mit Kondensatverdunstung Bestell Nr.	43152101
Verpackungsmaße	1,015 x 443 x 295 mm
Bruttogewicht	49.5 kg
Taric code	84158200
GTIN (EAN)	5350604360679